


## xSpan RAIN RFID Gateway

The Impinj xSpan gateway is a fixed-infrastructure RAIN RFID reader system that reduces business operational costs and maximizes sales through constant, accurate inventory visibility.



# Real-time Inventory Management, Always-On Asset Tracking

Ideal for inventory management, asset tracking and dock door solutions in retail, healthcare, and supply chain, the xSpan gateway simplifies RAIN RFID reader installation and management, lowering the total cost of infrastructure ownership.



The Impinj Platform includes Connectivity Devices



### xSpan Benefits

#### **Continuous, Hands-free Monitoring**

Installs overhead or on walls to automatically monitor items within a rectangular space for always-on connectivity

#### Real-Time Item Identification and Movement

Monitor inventory and track item movement along a single axis

#### Plug and Play

Integrated system streamlines the deployment process and minimizes installation costs

#### **Key Features**

#### > Rectangular Area Monitoring

A single xSpan gateway has a field of view up to 1,000 ft<sup>2</sup> (93m<sup>2</sup>); coverage extended with multiple gateways

#### **▼** Track Movement in Real-Time

Track movement in one dimension

#### **▶** Platform Ready

Leverage ItemSense software for large-scale data aggregation and device management

#### **Use Cases**



#### **Supply Chain**

Monitor tagged items, pallets, equipment, files or people passing through doorways, hallways, or other zonal coverage areas



#### **Asset Tracking**

Increase asset availability while reducing labor costs and inefficiencies due to manual cycle counts



#### **Shipment Verification**

Improve efficiency by ensuring accurate material flow from receiving, through production, and out dock doors





#### **Gateway Family Overview**

Impinj gateways combine industry-leading reader performance with advanced antenna arrays to continuously identify items and their locations within large areas. The Item Intelligence gathered provides inventory accuracy for retailers, shows real-time asset location for healthcare providers and gives logistics companies visualization into their global supply chain.

Product Details	xSpan Gateway	xArray Gateway	xPortal Gateway	
Recommended Usage	Portals and entrances	Portals and entrances	Portals and entrances	
	Room monitoring	Large area monitoring		
	Movement detection	Movement detection		
		Locating item		
Air Interface Protocol	RAIN RFID: EPCglobal UHF RFID Class 1 Gen2v2 / ISO 18000-63			
Number of Antenna Beams	13	52	2	
Operating Modes	Inventory (tag monitoring)	Inventory (tag monitoring)	Inventory (tag monitoring)	
	Tag Direction (track tags as they move through sectors along a single axis)	Tag Direction (track tags as they move through sectors along two axes)		
Coverage Area (typical)	≤ 1,000 ft² (93 m²)	≤ 1,500 ft² (139 m²)	≤ 700 ft² (65 m²)	
Dimensions	18.8 x 8.7 x 3.5 in (48 x 22 x 9 cm)	18 x 18 x 3 in (46.7 x 46.7 x 7.5 cm)	30.5 x 8.75 x 2 in (77.5 x 22.2 x 5 cm)	
Weight	7.6 lbs (3.4 kg)	17.8 lbs (8.0 kg)	6.5 lbs (3 kg)	
Max Receive Sensitivity	-84 dBm			
Supported Regions	For a list of supported regions and geograpies please go to: <a href="https://www.impinj.com/supported_regions">www.impinj.com/supported_regions</a>			
Software supported	Octane SDK (.NET and Java), LTK (C, C++, .NET, Java), ItemTest, ItemSense			
3dB beam width - sum of all antenna beams	FCC: 116° major axis, 75° minor axis EU: 120° major axis, 83° minor axis	FCC: 116° major axis EU: 120° major axis	120° major axis, 80° minor axis	
Mounting	Vesa 75, Vesa 200 x 100, or Direct Attach	Vesa 200 or Direct Attach	Vesa 75, Vesa 100, Keyhole slots or Direct Attach	
Sealing / Temperature / Humidity		IEC IP50 / Operating -20°C to 50°C; Storage -20°C to 50°C / 5% to 95% non-condensing IEC IP52 / Operating -20°C to 50°C; Storage -20°C to 50°C / 5% to 95% non-condensing		
GPIO support	NO	NO	YES	
Management Interface	, , , , , ,	Impinj Web UI; Impinj Rshell Management Console using console port or SSH; SNMPv2/v3 MIBII; EPCglobal Reader Management v1.0.1; Syslog		
Network Connectivity		10/100BASE-T		
RoHS Compliant	YES			
Power Sources	802.3af PoE or AC-DC power supply rated for 24Vdc/2.1A			
Power Consumption	Idle 7 W; Maximum power 15.4 W			

Ready to discuss how Impinj can help your business?

CONTACT US / WWW.IMPINJ.COM

Impinj (NASDAQ: PI) wirelessly connects billions of everyday items such as apparel, medical supplies, and automobile parts to consumer and business applications such as inventory management, patient safety, and asset tracking. The Impinj platform uses RAIN RFID to deliver timely information about these items to the digital world, thereby enabling the Internet of Things.

